

Bleeding and Venting Valves

Combined Bleeding and Venting Valves GOLIA 3F (EB 1.76)



Valve made of Duplex or Superduplex

Technical Data

Connection G	1, 2
Connection DN	50 - 200
Nominal Pressure PN	10 - 40
Operating Pressure	0.2 - 40 bar
Flow Rate	venting up to 11800 Nm ³ /h bleeding up to 12500 Nm ³ /h continuous bleeding up to 90 Nm ³ /h
Temperature	60 °C
Medium	aggressive fluids

Description

Bleeding and venting valves remove air or gases from systems or pipelines without requiring an external energy input. When a system is drained they act as venting valves.

GOLIA 3F (EB 1.76) is a combined startup and continuous bleeding and venting valve with guided float. During startup large air quantities are discharged at low pressure via a large seat. If the bleeding valve is closed and further small volumes of air accumulate during continuous operation, a second seat arranged within the float opens and discharges the accruing air. The large cone does not open until the level is going down at simultaneous pressure release. In the event of a vacuum the valves open immediately.

The bleeding and venting valves GOLIA 3F (EB 1.76) are float-controlled compact devices for aggressive fluids. The body is made of Duplex or Superduplex. The valve cone is soft sealed. The minimum pressure required for valve seal is 0.2 bar.

Maintenance work can be done from above at the installed valve.

Standard

- » Pressure stage PN 16
- » Designed acc. to EN-1074/4 and AWWA C-512
- » Flanges as per EN 1092/2
- » Body made of Duplex or Superduplex
- » Float made of polypropylene PP
- » Seals made of EPDM, FKM or silicone
- » Outlet with protection cover

Options

- » Pressure stage PN 10, 25, 40
- » Degassing bend made of polypropylene PP, 1.4401 / 316 for DN 200
- » Non-slam closing mechanism
- » Pressure surge attenuation by anti-shock system
- » Dirty water version
- » Purging connection
- » Flanges acc. to ANSI
- » Other flanges and seal materials on request
- » Closing pressure 0.1 bar
- » Bigger nominal diamters up to DN 400 on request

Operating instructions, know how and safety instructions must be observed. The pressure has always been indicated as overpressure. We reserve the right to alter technical specifications without notice.



Air Flow Rate Nm³/h

	ΔP bar	nominal diameter DN							
		G 1	G 2	50	65	80	100	150	200
venting	0.05	80	300	300	300	800	1200	3000	5000
	0.1	120	450	450	450	1100	1700	4000	7000
	0.3	200	750	750	750	1800	3000	6100	11800
start-up bleeding	0.05	80	300	300	300	750	1200	2800	4500
	0.1	110	450	450	450	1100	1800	4000	7000
	0.3	200	750	750	750	2000	3000	7000	12500
continuous bleeding	2	2	2	2	2	2	4	11	18
	6	4	4	4	4	5	7	18	36
	8	6	6	6	6	7	11	29	54
	10	6	6	6	6	8	13	36	65
	16	8	8	8	8	13	18	54	90

Bleeding and Venting Valves

Combined Bleeding and Venting Valves GOLIA 3F (EB 1.76)



Valve made of Duplex or Superduplex

Materials

Body	Duplex, Superduplex
Flanges	Duplex, Superduplex
Seat	Duplex, Superduplex
O-Rings	EPDM / FKM / silicone
Float	polypropylene
Spacer	Duplex, Superduplex
Deflector	Duplex, Superduplex
Cap, Screen	1.4401 / 316
Nuts	1.4401 / 316
Drain valve	1.4401 / 316
Studs	1.4401 / 316

Dimensions Sleeve Connection [mm]

size	G 1	G 2
A	95	165
B	200	255
B1	285	380
D	G 1	G 2

Dimensions Flange Connection [mm]

size	DN 50	DN 65	DN 80	DN 100	DN 150	DN 200
A	165	185	200	235	300	360
B	255	255	285	335	445	515
B1	380	380	435	510	650	830
C	40	40	50	50	70	70
D	G 2	G 2	G 2 1/2	G 3	G 4	G 6

Weights with Protection Cap [kg]

G 1	G 2	DN 50	DN 65	DN 80	DN 100	DN 150	DN 200
6.5	6.5	8	8	12	17	45	62

Weights with Degassing Bend [kg]

nominal diameter							
G 1	G 2	DN 50	DN 65	DN 80	DN 100	DN 150	DN 200
7	8	9.5	9.5	13.5	20	51.5	78.5

Customs Tariff Number

84818059

Special designs on request.

The pressure has always been indicated as overpressure.

Mankenberg reserves the right to alter or improve the designs or specifications of the products described herein without notice.

Dimensional Drawing

